


CMR608

5.25" two-way loudspeaker



The CMR608 is a 5.25" low impedance two-way built-in speaker with an excellent HiFi sound and a rectangular shape. It can be used with every standard HiFi amplifier and is reliable, even at high power use. With its warm and complete sound, the CMR608 is ideal for speech and music reproduction.

The housing is made of ABS. It has a 5.25" polypropylene woofer and 1" tweeter.


The speaker itself is made of treated paper cone and therefore the CMR608 is moisture proof.

Mounting is very easy due to the 4 screws, which are hidden behind the speaker grille. Because of that the CMR608 has a modern and unobtrusive design. The CMR608 loudspeakers can be painted in any colour.


TECHNICAL SPECIFICATIONS

height in mm	170	width in mm	237
depth in mm	60	cutout in mm	146 x 213
installation grip range in mm	3 - 17	loudspeaker system	2-way
woofer size in inch	5.25	woofer cone material	polypropylene
tweeter size in inch	1	mounting system	4 screws
colour	white	impedance in ohms	8
low impedance dynamic power in watts	60	low impedance RMS power in watts	40
SPL 1W/1m in dB	92	max SPL 1m in dB	108
frequency response in Hz	60 - 20K	main construction material	ABS plastic
grille main material	aluminium	IP rating	
applicable low impedance	yes	applicable in 100V	no
Horizontal dispersion angle 1000 Hz	180°	Vertical dispersion angle 1000 Hz	180°
closest RAL colour (subject to deviations)	RAL9010	Net weight product in kg	1.00

MORE PICTURES




ACCESSORIES



T60

8 ohms / 100 volt transformer, 60 watts



T20

8 ohms / 100 volt transformer, 20 watts



CMRBBI

In-wall box for CMR loudspeaker range



CMRBB

on-Wall box for CMR loudspeaker range