

36-730 CANARE L-2.5CHWS CABLE Black (reel of 200m)



Flexible and durable suitable for mobile HD and UHD applications.
 Designed for withstanding repeated bending.
 Stranded center conductor.
 Double-braided shield.
 High density dielectric insulation.

Cable Size Group	Not in Canford scheme. (See 'Connectors & Tooling' below)		
Inner conductor:	7/0.2mm	(0.6mm O.D.	24AWG)
Dielectric :	2.6mm O.D.		
Screen 1:	0.10mm/8/16	(95% or more)	Braid
Screen 2:	0.10mm/9/16	(94% or more)	Braid
Construction:	Coaxial cable		
Jacket material:	PVC		
Overall diameter:	4.2mm		
Impedance:	75 ohms		
Capacitance:	53 pF/m		
Inner conductor resistance:	8.5 Ω/100m		
Screen resistance:	1.0 Ω/100m		

Attenuation:

MHz	10	30	72	88	135	180	270	750	1300	1500	3000	6000
dB/100m	4.00	7.00	10.90	12.10	15.10	17.50	21.70	37.40	50.50	54.70	81.00	121.90

Weight:	3.2kg/100m
Reel Length:	200m

Connectors & Tooling:

- 48-5064 COAX CONNS 10-005-W126-EJ1 BNC 12G Male cable crimp, 75 ohm, Canare L-2.5CHWS
- 48-5074 COAX CONNS 10-005-W126-EJ1 BNC 12G Male cable crimp, 75 ohm, Canare L-2.5CHWS (100 pack)
- 55-8187 COAX CONNS 96-HTS-77 CRIMP TOOL with cavities 1.07, 4.52, 6.48, 7.06mm AF (EF, EF1, FB1, FC1)

- 48-6372 NEUTRIK NBNC75BFG7X BNC 12G UHD Male cable, rear twist, group X
- 48-574 NEUTRIK HX-R-BNC CRIMP TOOL (without die-set)
- 48-563 NEUTRIK DIE-R-BNCX-PDG DIE SET For HX-R-BNC crimp tool

- 48-6371 NEUTRIK NBNC75BDD6X BNC 12G UHD Male cable, rear twist, Belden 1855A, Canare L2.5CHWS
- 48-574 NEUTRIK HX-R-BNC CRIMP TOOL (without die-set)
- 48-560 NEUTRIK DIE-R-BNC-PDC DIE SET For HX-R-BNC crimp tool