

## 24615 Lighting/Speaker stand

### Product variant

24615-000-55 - black

### Data

Base diameter	1550 mm
EAN	4016842117055
Height	from 1,755 to 3,000 mm
Height adjustment	hand crank with push-button system and locking screw
Leg construction	tube legs with double cross braces
Material	aluminum
Max. load capacity*	35 kg
Number of legs	3
Product Category	Starline
Rod combination	2-piece folding design
Size when folded	1,733 x 202 x 150 mm
Special features	steel extension tube; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Type	black
Weight	8 kg



High-quality aluminium light stand for professional use. The height adjustment from 1,755 to 3,000 mm is comfortable and safe thanks to a crank mechanism with »Auto Lock« locking system. The ergonomic operation proves to be simple and user-friendly. The robust stand is focused on stability and steadiness, so that the 5° stability test according to DIN 56950-3 with a load capacity of 35 kg is easily achieved. The compact transport dimensions are 1,733 x 150 x 202 mm and the weight is approx. 8.0 kg. The integrated M10 threaded bush can be used to directly mount additional trusses or individual spotlights.