

Specifications Stack Light

Input	<ul style="list-style-type: none"> • XLR 3-pole for <ul style="list-style-type: none"> - power supply - XL2 digital I/O signal • 6.3 mm jack plug for standard foot switch connection
Visual Indications	<ul style="list-style-type: none"> • Level light indication in green, orange and red (limit setting in XL2) • Power Indication LED
Cable Adapter	<ul style="list-style-type: none"> • Adapter length = 20 cm • Assignment: <ul style="list-style-type: none"> 1 - Ground 2 - Power Supply 3 - Digital I/O
Power Supply	The default XL2 Power Adapter powers the XL2 and the Stack Light at the same time
Scope of Supply	<ul style="list-style-type: none"> • Stack Light • Cable Adapter
Extension Cable (not included)	<ul style="list-style-type: none"> • Cable adapter can be extended with standard XLR cable • Maximum cable length typically 40 m
Cascading	Up to 10 I/O Devices can be cascaded @ one single XL2 (cabling not included)
Dimensions (L x W x H)	120 x 120 x 260 mm
Weight	360 g, 0.8 lb
Temperature	-10 °C to +50 °C (14° to 122 °F)
Humidity	< 90% RH (non-condensing at 50 °C, 122 °F)
Standards	CE compliant: EN 61326-1 Class B, EN 55011 class B, EN 61000-4-2 to -6 and -11 Safety EN 60 065, EN 61 010-1:2001, class II
Protection Rating	IP51
NTi Audio #	600 000 610

All information subject to change without notice.

Configuration

