

www.skb-europe.com The Transport Authority +31 (0)497 - 339836

Product specification sheet

3I-2424-10B-C null Product title



Description

SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket sealed, water and dust tight, submersible design (MIL-C-4150J / IP67) that is resistant to corrosion and impact damage. Features include a molded-in hinge, patented trigger release latch system, comfortable, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD-648C), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD-810G).

Features

- Waterproof and dust tight design (MIL-C-4150J / IP67)
- ٠ Trigger release latch system
- · Convenient push button release pull handle
- · In-line skate style wheels for easy transport
- Trigger release latches can be retrofitted with TSA accepted key locking latches
- · Padlock holes include stainless steel padlock protector clips
- · Molded-in hinge for added protection
- Snap-down rubber over-molded cushion grip handle
- Ambient pressure equalization valve (MIL-STD-648C) Resistant to UV, solvents, corrosion, fungus (MIL-STD-810G)
- Resistant to impact damage (MIL-STD-810G)

Specifications

Interior Length	61.0 cm	24.1 inch
Interior Width	61.0 cm	24.1 inch
 Interior Height 	25.4 cm	10.0 inch
Base Depth	25.3 cm	10.0 inch
Lid Depth	5.1 cm	2.1 inch
 Exterior Length 	67.3 cm	26.5 inch
Exterior Width	67.5 cm	26.6 inch
 Exterior Height 	29.6 cm	11.7 inch
 Carton Length 	68.6 cm	27.1 inch
Carton Width	68.6 cm	27.1 inch
 Carton Depth 	31.8 cm	12.6 inch
 Shipping Weight 	13.9 kg	30.6 lb
 Product Weight 	12.6 kg	27.8 lb
Cubed Foam		

versatile|indestructable|guaranteed

SKB Europe bv P.O. Box 209 Hamelendijk 2 Reusel

5540 AE Reusel The Netherlands ► T +31 (0)497 339836 F +31 (0)497 380719 E info@skb-europe.com Bank 13.79.45.981 BTW NL 8203.08.468.B01 KvK Eindhoven 17239118 IBAN NL38 RABO 0137945981 BIC RABO NL 2U

