ECM-90LM

Electret condenser microphone



Overview

Ultra-miniature, omni-directional electret condenser lavalier microphone designed for quality-critical applications in ENG, Studio, EFP, and Location Sound applications. Dual diaphragm design contributes to high sensitivity, wide dynamic range, and low noise. Generous diaphragm mounting architecture radically reduces common cable noise associated with lavalier microphone designs. Flat and wide frequency response (20Hz – 20kHz) provides natural sound reproduction. Water resistant design maintains sound clarity in almost any application or environment. Shielded for use with digital wireless transmitters.

Specifications

Audio Section	
Capsule Type	Electret Condenser
Frequency Response	20 Hz to 20 kHz
Directivity	Omni-directional
Sensitivity *[1]	– 40 dB (10mV)
Output Impedance	

© 2004 - 2021 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.



*[2]	6.3 kΩ (unbalanced)
Dynamic Range (typ.)	99 dB
Signal-to-Noise Ratio (typ.) *[3]	68 dB
Inherent Noise (typ.) *[4]	26 dB SPL
Wind Noise *[5]	45 dB SPL or less (with supplied windscreen)
Maximum Input Sound Pressure Level (typ.) *[6]	125 dB SPL

General Section	
Connector	3-pin Lemo connector
Mic Cable	5.2 feet 1.6m
Power Requirements	Supplied from Sony wireless system transmitters
Dimensions *[7]	5/32 x 5/32 x 21/26 inches (Mic head) 3.5 x 3.5 x 20.5 mm (Mic head)
Mass (microphone body, excluding cable)	Approx. 0.035oz Approx. 1g
	Urethane type windscreen (1)

^{© 2004 - 2021} Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.

Supplied Accessories	Single/vertical type tie clip (1) Single/horisontal type tie clip (1) Operating instructions (1)
Optional Accessories	Wind screen pack Vertical clip pack Safety clip pack Horizontal clip pack Double clip pack Color windscreen pack Black windscreen pack Accessory kit

Notes	
*[1]	0 dB = 1 V/Pa, at $1 kHz$
*[2]	Output impedance at 1 kHz
*[3]	A-weighted, 1 kHz, 1 Pa
*[4]	0dB SPL = 20 μ Pa
*[5]	Wind noise at 2m/s (0 dB SPL = 20 μ Pa)
*[6]	0dB SPL = 20 μPa
*[7]	The values for dimensions are approximate.

Related products



DWT-B03R

DWX Series digital wireless microphone bodypack transmitter

Gallery

