

PC-1860BS

The ceiling speakers of the PC-series are suitable for announcements and BGM system use in high quality. The speaker's design harmonizes with modern architecture and decor. The PC-1860BS is equipped with a fire dome to protect it from fire and to prevent fire from spreading through the ceiling. Thus, the speaker is designed according to British Standard BS 5839-8: 2008 and EN54-24.



Order no: PC-1860BS

Specifications

Frequency response	170 Hz - 20 kHz (peak -20 dB)
Connection	2-Steatite connector (3 pole)
Sensitivity (1#V, 1#n)	95 dB (500 Hz - 5 kHz, pink noise)
Speaker component	12 cm cone-type
Rated input (High Impedance)	6 W (100 V), 3 W (70 V)
Tappings	100 V: 1.7 k Ω (6 W) / 3.3 k Ω (3 W) / 6.7 k Ω (1.5 W) / 13 k Ω (0.8 W) 70 V: 1.7 k Ω (3 W) / 3.3 k Ω (1.5 W) / 6.7 k Ω (0.8 W) / 13 k Ω (0.4 W)
Mounting hole	156,00 mm
Dimensions (W x H x D)	x 105
Dimensions (ϕ x D)	180 x 105 mm
Finish	Steel plate, paint, traffic white (RAL 9016 or equivalent) Grille: Steel net, paint, white (RAL 9016 or equivalent) Fire dome: Steel plate, paint, black
Operating temperature	-10 °C to +50 °C



EN 54 certified speakers

PC-1860BS

Appearance