



Simple design. Big in sound.

Designed to fit any head contour and to free performers to focus on their performance! Perfect for stage, broadcast, public address and presenters.

Its Omni pattern is less prone to "popping" and wind noise and excels with clear and natural voice reproduction. A perspiration drip ring on the gooseneck ensures the microphone capsule stays dry at all times.

The VT700 is a very comfortable, lightweight and unobtrusive headworn. The flexible gooseneck enables the user to position the microphone for optimum sound and gain before feedback. The cable runs neatly behind the neck for maximum concealment.

Colors: beige

Application area: Presentations - Theatre - Broadcast-Studio

The VT700 comes in an elegant black case with the following accessories:

STRAP	Colors: beige or black
WS400/700	Windsccreen (OPTIONAL Colors: beige or black
Case4	Size: 190x210x100mm

Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland Phone: +41 44 432 32 30, Email: info@vt-switzerland.com

Specifications				
Generating Element:	Electret Condenser			
Polar pattern:	Omni-Directional			
Frequency Range:	50Hz- 18kHz			
Sensitivity (@1kHz):	-33dB ±3dB 1V/microbar (22.4mV/Pa)			
Noise Level	27dB "A" weighted			
Max. Input SPL:	115dB			
Impedance:	2.8 to 6.8 kOhms, nominal 4.4 kOhms			
Bias/+VDC:	1.5V to 9.0V (max.)			
Dynamic Range:	88dB			
Signal Noise Ratio:	67dB @94dB SPL			
Color:	beige			
Cable:	Length 1,5m Ø 2mm			
Weight;	17 g			

Wiring Configuration (3-wire):	
Red	+VDC
Соррег	Ground
Blue (Transparent)	NF
Wiring Configuration (2-wire):	
Red + Blue (Transparent)	NF + +VDC
Соррег	Ground
15 10 5 10 100 200 1000 2000 Frequency Response (Hz)	5000 10000 20000